## **NOVA POWER PRODUCT MATRIX**











Product Series	Power Conditioning	Battery Backup	19" Rackmount Avail.	Input Voltage	Output Voltage	Availabilty Capacity	Height Range	Width Range	Length Range	Available Connectors
48 VDC Series	x	х	✓	92-155VAC 42-60VDC	54VDC	2800VA/2400W	1¾"	17"	22"	MIL-SPEC
Battery & Battery Backup			Please ask	for addition	nal informat	ion on Batter	y and Batte	ery Backup		
Hot Swappable Series	✓	✓	✓	80-265VAC (22-32VDC*)	120VAC	1250VA/1000W 2400VA/1680W 2800VA/2400W	1¾"-5 ¼"	17"-19"	17" - 22½"	MIL-SPEC
Industrial Series	✓	✓	✓	80-150VAC	120VAC	1000VA/800W 2000VA/1600W 3000VA/2400W	1.7" - 5.25"	17" - 19"	14"-24"	NEMA
NP Series	✓	✓	✓	85-155VAC	120VAC	560VA/400W 1250VA/1000W	1.7"	11"-15"	8.5"	NEMA
SRN Series	✓	<b>√</b>	✓	92-155VAC	120VAC	1500VA/1050W 2000VA/1400W	5¼"	19"	21"	NEMA
SRNDT(I) & UPR Series	✓	✓	✓	92-250VAC	120VAC	1250VA/875W 1500VA/1050W 2000VA/1400W 2400VA/1680W 4000VA/3360W	5¼"-7"	19"	23"-25"	NEMA, CPC, MIL-SPEC, Terminal Block
SRNSL (I,X) Series	✓	✓	✓	92-155VAC	120VAC	2500VA/2000W 1250VA/1000W 2800VA/2400W	3½"	19"	20"-25"	NEMA, MIL-SPEC
Tower Mount Series	✓	✓	✓		115-120VAC (24,28VDC*)	1250VA/1000W 2000VA/1400W	9"-14"	7"	21"	NEMA, MIL-SPEC, Terminal Block